

MORTAR MIXER INSTRUCTIONS

Towing:

1. Do not tow the mixer unless the tow pole is bolted in place and safety bolt on end of tow pole is securely fastened.
2. Securely fasten hitch to towing vehicle.
3. Safety chains must cross undertow pole and be positioned to prevent the tow pole from dropping to the ground in event of a hitch failure.
4. Lock the drum in tow position.
5. Never tow the mixer over 55 MPH! Do not tow unless mixing drum is empty!

Starting:

1. Be sure the belt slip lever is in the "START/STOP" position.
2. Check to see that drum is clear of any obstacles and drum gate is closed.
3. Start engine and allow warming up for 1-2 minutes.
4. Close engine cover and latch both sides before putting belt slip lever in the "MIX" position.

Charging the mixer:

1. Place the ingredients into the drum in the following order, AFTER ENGAGING PADDLES:
 - A. Half of required water.
 - B. Half of required sand.
 - C. Required mortar cement or plaster.
 - D. Balance of water.
 - E. Balance of sand.
2. After discharging batch, immediately add half of required water for next batch and let paddles turn in water a short time. This will keep both drum and paddles clean and prevent lumps in mix.
3. When finished thoroughly clean the mixer. You will be charged a cleaning charge if machine is not cleaned before return!

Stopping the mixer:

1. Put belt slip lever in "START/STOP" position.
2. Push STOP button on engine cover till engine stops.